



YUPOTako® – A new temptation for the creative appetite

Tako means Octopus in Japanese. The new YUPOTako® sticks to flat surfaces just like an octopus, due to its micro suction structure. It uses no adhesive, leaving no sticky feeling on the label.

Characteristics of YUPOTako®

- Bubble free.
- Special handling or application is not required.
- Easy to stick on and easy to remove.
- Not using glue, so there is no sticky feeling and does not leave any glue on the surface due to the micro suction structure.
- The backside of YUPOTako® can be washed with water when the adhesion is weakened by dust, and it can be used correct as many times as you want.
- Not using PVC. YUPOTako® is environmentally friendly.
- Variety of grades for different printing methods.

YUPOTako® grades available:

Grade	Thickness (microns)	Basis weight (g/m ²)	Print method	Recommended ink type
WKFS 340	320	220	Sheet offset	Offset paper ink
XAD 1069	210	166	Screen print and UV digital	Screen: PP inks
WKJ 250	220	156	Waterbase Inkjet	Pigment
XAD 1071	285	224	Eco solvent Inkjet	Eco solvent
XAD 1058	240	170	HP Indigo	–
XAD 1057	272	190	Office Inkjet	–

Applications:

Advertisement for electrical appliances in shops, specially refrigerators and computers • Posters for department stores • Active campaigns at fast-food restaurants • Floor banners at supermarkets • Advertisement in vending machines • Kids games

Usage Instructions - Caution -

It is better to leave white material on mounting object (where YUPOTako® will be applied), when:

- Mounting object is printed plastic (especially PVC and Acrylic), and when leave YUPOTako® on the object for long time period;
- High temperature and high humidity such as 60°C / 90% Rh;

White material left on the mounting object is easily wiped off by wet towel.

Not suitable for sticking on 3D object. Not suitable for using as a sticker for cars, and for outdoor usage.

When laminating YUPOTako®, some curl can happen during applying or removal of the label.

Do not apply YUPOTako® on glasses with steel net wire. Due to the heat insulated on YUPOTako®, the glass might break. Do not apply YUPOTako® on Plasma TV's. It may cause image burn out on the display.

Available Sizes (Sheets):

Grade	Size	Packaging
WKFS 340 - Offset	640 × 900 mm, 640 × 450 mm & 1020 × 720 mm	100 sheets / ream
XAD 1058 - HP Indigo	460 × 320 mm	250 sheets / ream
XAD 1057 - Office Inkjet	A4 - 297 × 210 mm	100 sheets / ream

Available Sizes (Reels):

Grade	Size
XAD 1069 - UV Inkjet / Screen	1270 mm × 300 m
XAD 1069 - UV Inkjet / Screen	1270 mm × 20 m
WKJ 250 - Waterbase Pigment Inkjet	1270 mm × 20 m 914 mm × 20 m 610 mm × 20 m
XAD 1071 - Eco solvent Inkjet	1270 mm × 20 m

YUPO® EUROPE GMBH

Willstätter Str. 30
40549 Düsseldorf
Germany

Tel: +49 211 - 520 54 30
Fax: +49 211 - 520 54 368
www.superyupo.com

